wel-magnetic

- >Uni-directional, non-reversible
- >Dry dial counter
- >Vacuum sealed counter
- >Hermetically sealed counter
- >With anti-corrosive epoxy resin treated copper body
- >Clear, tempered glass cover
- >Easy to replace, non-corrosive strainer
- >With threaded tail piece

Specifications

>Meter size: 1/2" (15mm) >Maximum flow (Qmax): 3 m3/h >Nominal flow (Qn): 1.5 m3/h >Transitional flow (Qt): 120 l/h

>Minimum flow (Qmin): 30 l/h
>Starting flow (Qs): 16 l/h
>Minimum reading: 0.0001 m/3
>Maximum reading: 99999 m/3
>Nominal Pressure: 10 bar
>Headloss at Qmax: <1 bar
>TesT Pressure: <10 bar
>Maximum Temperature: 50°C

Weight and Dimension >Length: 259 (Lmm)

>Width: 165 (L1mm) x 98 (Dmm)

>Height: 114 (Hmm)

>Connecting thread: G3/4 (19mm) ISOR228"

>Weight: 1.8 kg.

Total ABC - Php 975,000.00

(Total Amount in Words): NINE HUNDRED SEVENTY FIVE THOUSAND PESOS ONLY.

Quoted by:

Supplier

Prepared by:

Ireen P. Reves

BAC Member

Noted by:

AUREA O. ADRADOS BAC Chairman

Terms & Conditions:

- As a government agency, BLWD shall deal only with a legitimate suppliers/contractors which issue BIR-registered official receipt;
- All quoted prices must be inclusive of 5% tax for materials & supplies; 6% for labor and 1% expanded withholding tax

Line Items

Item No.	Product/Service Name	Description	Quantity	MOU	Budget (PHP)
1	Water Service Connection Materials/Fittings	Supply and delivery of Seven Hundred Fifty (750) pieces (15mmØ) 1/2" Brass Water Meter for new service connections and meters for sale.	1	Lump Sum	975,000.00

Other Information

Important Note

- >Provide a copy of product description
- >Water meter must be factory calibrated (provide a valid certificate)
- >Supplier and product must be LWUA Accredited (provide a valid certificate)
- >Provide a copy of MWSI/MWCI/NWRB Certificate if any
- >Product should be in conformity with the international standard ISO 4064 and manufactured by an ISO 9000 and ISO 9001 quality accredited company (provide a valid certificate if any)