



BALANGA WATER DISTRICT
EGSA, Four-Lanes, Tuyo, Balanga City, Bataan 2100
Mobile No. +639-190-870-348



RFQ No.: 2023-027

REQUEST FOR QUOTATION

Name of Supplier:	Please quote us your lowest price of the following articles subject to the terms and conditions contained herein:
Address:	
Tel. No.:	
Fax:	

Item No.	Unit	Item Description	Qty	Unit Cost	Amount
	unit	Supply, delivery, installation, testing and commissioning of submersible electric motor 2HP 230V, Single Phase, 60 cycles suited for 4" diameter well or larger casing complete with cable guard and lead wire including labor for splicing	1		
	meters	Submersible Cable #12 3c	55		

TOTAL AMOUNT IN WORDS:

<p>Quoted by:</p> <p>_____</p> <p>Supplier</p>	<p>Requested by:</p> <p> AUREA D. ADRADOS BAC CHAIRMAN</p>
<p>Terms & Conditions:</p> <ol style="list-style-type: none">1. As a government agency, BLWD shall deal only with a legitimate suppliers / contractor which issue BIR-registered official receipt;2. All quoted prices must be inclusive of 5% tax for materials & supplies; 6% for labor and 1% expanded withholding tax	<p>Noted by:</p> <p> Engr. Charlito G. Rodriguez General Manager</p>

Scope of Work:

Supply, delivery, installation, testing and commissioning of submersible motor

Item Description:**1 unit**

Submersible electric motor 2HP 230V, Single Phase, 60 cycles suited for 4" diameter well or larger casing complete with cable guard and lead wire including labor for splicing

55 meters

Submersible Cable #12 3c

Warranty Conditions:

12 months for Submersible Motor from the date of installation

Submersible Motor Specifications:**Basic Features:**

1. Corrosion-resistant construction
2. Stainless steel splined shaft
3. Hermetically-sealed windings
4. StatorShield™ resin system
5. Filter check valve
6. Water lubrication
7. Kingsbury-type thrust bearing
8. Pressure-equalizing diaphragm
9. Sand fighting slinger
10. Built-in lightning arrestors (single-phase)
11. New lead assembly
12. UL 778 recognized (North American voltages)
13. CSA certified
14. ANSI/NSF 61 certified
15. Industry standard NEMA mounting dimensions

Technical Data:

1. 60Hz
2. 3-Wire
3. Hp Range - 2
4. kW Range – 1.5
5. Poles – 2
6. RPM – 3450
7. Max Ambient Temp - 86 °F / 30 °C
8. Duty Rating – Continuous at 0.25 ft/sec flow past motor

Dimensions and weights:

1. Length (inches) – 20.62
2. Shipping Weight – 19.5 kg / 43 pounds
3. Motor carton size (inches) – 6 x 6 x 25

Important Note:

1. Provide supporting documents of the item/s quoted (manufacturer product description, specification, and shop drawing)
2. Manufacturer of submersible motor must be more than 20 years in business