Scope of Work:

Supply, delivery, installation, testing and commissioning of submersible pump

Item Description:

1 unit

Submersible pump stainless steel impeller bowl and shaft suited for 5HP Motor 3450 rpm, 230 volts, Single Phase, 60 cycles capable of delivering 5 LPS x 55M. TDH

Warranty Conditions:

18 months for Submersible pump from the date of installation

Submersible Pump specifications:

Basic Features:

- · Stainless steel construction designed and built for years of trouble-free operation
- · Designed and built to operate in difficult conditions.
- All metal parts are made of 304 or 316 stainless steel, except for the shafts, which are made of 431, 304 or 316 stainless steel.
- Heavy duty stainless steel discharge head with built-in check valve for preventing back flow in connection with pump stoppage and the risk of destructive water hammer is reduced to a minimum.
- · Smooth safety hook
- · NEMA standard of bracket mounting.
- High quality shaft bearings provide low friction and high wear resistance.
- The stop ring prevents damage to the pump during transport and in case of up-thrust in connection with start-up. The stop ring, which is designed as a thrust bearing, limits axial movements of the pump shaft.
- Stainless steel strainer to restrict the entry of sand and other extraneous material.

Important Note:

- Provide supporting documents of the item/s quoted (manufacturer product description, specification, and shop drawing)
- 2. Manufacturer of submersible pump and motor must be more than 20 years in business

PAID
Name: Angeline M. Santos
Signature: Carter C
Date: JUN 2 9 2023