

Supply, delivery, installation, testing and commissioning of submersible pump.

Item Description:

1 unit

Submersible pump stainless steel impeller bowl and shaft suited for 15HP Motor 3450 RPM, 230 volts, three phase, 60 cycles capable of delivering **20lps x 40m TDH**.

Warranty Conditions:

18 months from the date of installation.

Submersible Pump specifications:

- Stainless steel construction designed and built for years of trouble-free operation.
- Designed and built to operate in difficult conditions.
- All metal parts are made of 304 or 316 stainless steel, except for the shafts, which are made of 431, 304 or 316 stainless steel.
- Heavy duty stainless steel discharge head with built-in check valve for preventing back flow in connection with pump stoppage and the risk of destructive water hammer is reduced to a minimum.
- Smooth safety hook.
- NEMA standard of bracket mounting.
- High quality shaft bearings provide low friction and high wear resistance.
- The stop ring prevents damage to the pump during transport and in case of up-thrust in connection with start-up. The stop ring, which is designed as a thrust bearing, limits axial movements of the pump shaft.
- Stainless steel strainer to restrict the entry of sand and other extraneous material.

Important Note:

1. Provide supporting documents of the item/s quoted (manufacturer product description, specification, and shop drawing).
2. Manufacturer of submersible pump must be more than 20 years in business.

PAID

Name: _____

Signature: _____

Date: OCT 24 2023