

Features:

- >Vane wheel
- >Multi-jet
- >Straight reading type
- >Made of selected high quality materials designed for Hot and Cold climate
- >Suitable for High and Low pressure area
- >Anti-magnetic
- >Uni-directional, non-reversible
- >Dry dial counter
- >Vacuum sealed counter
- >Hermetically sealed counter
- >With anti-corrosive epoxy resin treated copper body
- >Clear, tempered glass cover
- >Easy to replace, non-corrosive strainer
- >With threaded tail piece

Specifications:

- >Meter size : 1/2" (15mm)
- >Maximum flow (Qmax) : 3 m³/h
- >Nominal flow (Qn) : 1.5 m³/h
- >Transitional flow (Qt) : 120 l/h
- >Minimum flow (Qmin) : 30 l/h
- >Starting flow (Qs) : 16 l/h
- >Minimum reading : 0.0001 m³
- >Maximum reading : 99999 m³
- >Nominal Pressure : 10 bar
- >Headloss at Qmax : <1 bar
- >Test Pressure : <10 bar
- >Maximum Temperature : 50°C

Weight and Dimension:

- >Length : 259 (Lmm)
- >Width : 165 (L1mm) x 98 (Dmm)
- >Height : 114 (Hmm)
- >Connecting thread: G3/4 (19mm) ISO R228
- >Weight : 1.8 kg.