

BALANGA WATER DISTRICT
EGSA, Four-Lanes, Tuyo, Balanga City, Bataan 2100
Mobile No. +639-190-870-348

RFQ No.: 2024-011

REQUEST FOR QUOTATION	
Name of Supplier:	Please quote us your lowest price of the following articles subject to the terms and conditions contained herein:
Address:	
Tel. No.:	
Fax:	

Item No.	Unit	Item Description	Qty	Unit Cost	Amount
	unit	Supply, delivery, installation, testing and commissioning of submersible pump and motor with accessories for Pto. Rivas Itaas Pump Station.	1		

TOTAL AMOUNT IN WORDS:	
<p>Quoted by:</p> <p style="text-align: center;">_____</p> <p style="text-align: center;">Supplier</p> <p>Terms & Conditions:</p> <ol style="list-style-type: none"> 1. As a government agency, BLWD shall deal only with a legitimate suppliers / contractor which issue BIR-registered official receipt; 2. All quoted prices must be inclusive of 5% tax for materials & supplies; 6% for labor and 1% expanded withholding tax 	<p>Requested by:</p> <p style="text-align: center;"><u>AUREA O. ADRADOS</u> BAC CHAIRMAN</p> <p>Noted by:</p> <p style="text-align: center;"><u>Engr. Charlito G. Rodriguez</u> General Manager</p>

Scope of Work:

Supply, delivery, installation, testing and commissioning of submersible pump and motor with accessories

Item Description:**1 unit**

Submersible electric motor 3HP 230V, Single Phase, 60 cycles suited for 4" diameter well or larger casing complete with cable guard and lead wire including labor for splicing

1 unit

Submersible pump stainless steel impeller bowl and shaft suited for 3HP Motor 3450 rpm, 230 volts, Single Phase, 60 cycles capable of delivering **5 LPS x 30M TDH**

1 unit

Control box 3HP

30 meters

Submersible cable #10 3/c

1 roll

Suspension wire #18

3 pcs.

Compression connector

3 rolls

3M Rubber tape

3 rolls

Plastic tape

Warranty Conditions:

18 months from the date of installation

Submersible Pump specifications:

- Stainless steel construction designed and built for years of trouble-free operation
- Designed and built to operate in difficult conditions.
- All metal parts are made of 304 or 316 stainless steel, except for the shafts, which are made of 431, 304 or 316 stainless steel.

- Heavy duty stainless steel discharge head with built-in check valve for preventing back flow in connection with pump stoppage and the risk of destructive water hammer is reduced to a minimum.
- Smooth safety hook
- NEMA standard of bracket mounting.
- High quality shaft bearings provide low friction and high wear resistance.
- The stop ring prevents damage to the pump during transport and in case of up-thrust in connection with start-up. The stop ring, which is designed as a thrust bearing, limits axial movements of the pump shaft.
- Stainless steel strainer to restrict the entry of sand and other extraneous material.

Submersible Motor Specifications:

Technical Data:

1. 60Hz
2. 3-Wire
3. Hp Range - 3
4. kW Range – 2.2
5. Poles – 2
6. RPM – 3450
7. Max Ambient Temp - 86 °F / 30 °C
8. Duty Rating – Continuous at 0.5 ft/sec flow past motor

Important Note:

1. Provide supporting documents of the item/s quoted (manufacturer product description, specification, and shop drawing)
2. Manufacturer of submersible pump must be more than 20 years in business