

BALANGA WATER DISTRICT
EGSA, Four-Lanes, Tuyoy, Balanga City, Bataan 2100
Mobile No. +639-190-870-348



RFQ No.: 2024-044

REQUEST FOR QUOTATION

Name of Supplier:	Please quote us your lowest price of the following articles subject to the terms and conditions contained herein:
Address:	
Tel. No.:	
Fax:	

Item No.	Unit	Item Description	Qty	Unit Cost	Amount
	unit	Supply and delivery of one (1) unit Linux Server for Balanga Water District (Administrative Department)	1		

TOTAL AMOUNT IN WORDS:

<p>Quoted by:</p> <p style="text-align: center;">_____</p> <p style="text-align: center;">Supplier</p> <p>Terms & Conditions:</p> <ol style="list-style-type: none"> 1. As a government agency, BLWD shall deal only with a legitimate suppliers / contractor which issue BIR-registered official receipt; 2. All quoted prices must be inclusive of 5% tax for materials & supplies; 6% for labor and 1% expanded withholding tax 	<p>Requested by: </p> <p style="text-align: center;"><u>LORETO Q. PALAD</u> BAC CHAIRMAN</p> <p>Noted by: </p> <p style="text-align: center;"><u>Engr. Charlito G. Rodriguez</u> General Manager</p>
--	--

Full Specifications:

Processor:	One Intel Xeon E-2300 series processor with up to 8 cores per processor One Intel Pentium processor with up to 2 cores per processor
Operating System:	Canonical Ubuntu Server LTS Citrix Hypervisor Microsoft Windows Server with Hyper-V RedHat Enterprise Linux SUSE Linux Enterprise Server VMware ESXi
Chipset:	Intel® C256 series
Memory:	DIMM Speed Up to 3200 MT/s
Memory Type:	UDIMM
Memory Module Slots:	4 DDR4 DIMM slots
Maximum RAM:	UDIMM 128 GB
Storage:	Front Bays Up to 4 x 3.5-inch cabled SAS/SATA (HDD/SSD) max 30.72 TB
Storage Controllers:	Internal Controllers PERC H345, PERC H755, HBA355i External Controllers HBA355e, 12 Gbps SAS Ext. HBA
Software RAID:	S150
Internal Boot:	USB or Boot Optimized Storage Subsystem (BOSS-S1): HWRAID 2 x M.2 SSDs 240 GB or 480 GB
Security:	Cryptographically signed firmware Secure Boot Secure Erase Silicon Root of Trust System Lockdown (requires iDRAC9 Enterprise or Datacenter) TPM 1.2/2.0 FIPS, CC-TCG certified, TPM 2.0 China NationZ
Management:	Embedded / At-the-Server iDRAC9 iDRAC Service Module iDRAC Direct
Consoles:	OpenManage Enterprise OpenManage Power Manager plugin OpenManage SupportAssist plugin OpenManage Update Manager plugin
Mobility:	OpenManage Mobile
Tools:	iDRAC RESTful API with Redfish RACADM CLI IPMI System Update Utility Update Catalogs
OpenManage Integrations:	BMC Truesight Microsoft System Center RedHat Ansible Modules VMware vCenter and vRealize Operations Manager
OpenManage connections:	IBM Tivoli Netcool/OMNibus IBM Tivoli Network Manager IP Edition Micro Focus Operations Manager Nagios Core Nagios XI

Power Supplies: 300 W Bronze AC/100-240 V
Cabled power supply

Ports: Network Options
2 x 1 GbE LOM

Front Ports: 1 x Dedicated iDRAC Direct micro-USB
1 x USB 3.0

Rear Ports: 5 x USB 2.0
1 x USB 3.0
1 x VGA
1 x Serial Port
1 x iDRAC dedicated NIC port
2 x NIC port

Internal ports: 1 x USB 3.0 (optional)

Slots: PCIe
2 x PCIe Gen4 slots and 2 x PCIe Gen3 slots

Chassis: One fan

Bezel: Security bezel

Form Factor: 4U mini tower server

Dimensions & Weight: Height: 14.17 in. (360 mm)
Width: 6.88 in. (175 mm)
Depth with Bezel: 33.48 in. (453.75 mm)
Weight: 25.74 lbs. (11.68 kg)

Warranty Conditions:

Warranty must be 12 months or more against factory defects

Important Note:

1. Provide supporting documents of the item/s quoted (manufacturer product description, specification, and shop drawing)